# Product data sheet
## Characteristics

# XVGB3SW
Monolithic tower lights, Harmony XVG, 60mm, red orange green, steady light, buzzer, base mounting, IP42, 24V AC/DC



## Main

| | |
|---|---|
| Range of product | Harmony XVG |
| Product or component type | Complete pre-wired monolithic tower light |
| Beacon or indicator bank unit type | 3 illuminated units |
| Material | PC (UL94 V-2): globe<br>ABS (UL94HB): tube body<br>Aluminium: tube |
| Mounting diameter | 60 Mm |
| Component name | XVG |
| Device mounting | Base mounting |
| Light source | LED steady red<br>LED steady green<br>LED steady amber |
| Light block color | Red/Orange/Green |
| Indicator bank base type | Base with integrated buzzer |

## Complementary

| | |
|---|---|
| [Us] rated supply voltage | 24 V AC/DC |
| Cable cross section | 0.33 Mm² |
| Discrete output type | PNP and NPN |
| [Uimp] rated impulse withstand voltage | 0.5 KV |
| Current consumption | 180 mA |
| Noise level | 85 DB |
| Power consumption in W | 4.1 W |
| Fundamental frequency | 2.64 KHz |
| Net weight | 0.25 Kg |

## Environment

| | |
|---|---|
| Product certifications | CE[RETURN]EAC |
| Ambient air temperature for storage | -35…70 °C |
| Ambient air temperature for operation | -10…50 °C |
| IP degree of protection | IP42 |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.926 Cm |
| Package 1 Width | 8.002 Cm |
| Package 1 Length | 31.039 Cm |
| Package 1 Weight | 350.0 G |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 21 |
| Package 2 Height | 30 Cm |
| Package 2 Width | 40 Cm |
| Package 2 Length | 60 Cm |
| Package 2 Weight | 8.591 Kg |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 84 |
| Package 3 Height | 75 Cm |
| Package 3 Width | 60 Cm |
| Package 3 Length | 80 Cm |
| Package 3 Weight | 43 Kg |

## Offer Sustainability

| | |
|---|---|
| Recyclability potential, in % | 9 |
| Total lifecycle Carbon footprint | 35 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 3.7156209123 |
| Carbon footprint of the manufacturing phase [A1 to A3] | 4 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0.1222196436 |
| Carbon footprint of the distribution phase [A4] | 0.1 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.102232865 |
| Carbon footprint of the installation phase [A5] | 0.1 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 30.4040625 |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 30 kg CO2 eq. |
| Mercury free | Yes |
| Sustainable packaging | No |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.7085952994 |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.7 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |
| Total lifecycle Carbon footprint | 35 |
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| EU RoHS Directive | Compliant By Exemption |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which |
| End of life manual availability | End Of Life Information |
| Take-back | No |

## Contractual warranty

| | |
|---|---|
| Warranty (in months) | 18 |

Product Life Status : Commercialised