Product data sheet
Characteristics

XVGB3W
Monolithic tower lights, Harmony XVG, 60mm, red orange green, steady light, base mounting, IP53, 24V AC/DC



Main

Range of product	Harmony XVG
Product or component type	Complete pre-wired monolithic tower light
Beacon or indicator bank unit type	3 illuminated units
Material	PC (UL94 V-2): globe ABS (UL94HB): tube body Aluminium: tube
Mounting diameter	60 Mm
Component name	XVG
Device mounting	Base mounting
Light source	LED steady red LED steady green LED steady amber
Light block color	Red/Orange/Green
Indicator bank base type	Base without buzzer

Complementary

[Us] rated supply voltage	24 V AC/DC
Cable cross section	0.33 Mm²
Discrete output type	PNP and NPN
[Uimp] rated impulse withstand voltage	0.5 KV
Current consumption	109 mA
Power consumption in W	3.1 W
Fundamental frequency	2.64 KHz
Net weight	0.24 Kg

Environment

Product certifications	CE[RETURN]EAC
Ambient air temperature for storage	-35…70 °C
Ambient air temperature for operation	-10…50 °C
IP degree of protection	IP53

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	31.0 Cm
Package 1 Width	8.5 Cm
Package 1 Length	7.5 Cm
Package 1 Weight	349.0 G
Unit Type of Package 2	S04
Number of Units in Package 2	21
Package 2 Height	30 Cm
Package 2 Width	40 Cm
Package 2 Length	60 Cm
Package 2 Weight	8.61 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	84
Package 3 Height	75 Cm
Package 3 Width	60 Cm
Package 3 Length	80 Cm
Package 3 Weight	79 Kg

Offer Sustainability

Recyclability potential, in %	9
Total lifecycle Carbon footprint	35 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	3.7050048525
Carbon footprint of the manufacturing phase [A1 to A3]	4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1218704446
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1019407711
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	30.65125
Carbon footprint of the use phase [B2, B3, B4, B6]	31 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.7065707414
Carbon footprint of the end-of-life phase [C1 to C4]	0.7 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	35
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
End of life manual availability	End Of Life Information
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised