Product data sheet
Characteristics

XVGM3SM
Monolithic tower lights, Harmony XVG, 60mm, red orange green, steady light, buzzer, aluminium tube, foldable bracket, IP40, 220…240V AC



Main

Range of product	Harmony XVG
Product or component type	Complete pre-wired monolithic tower light
Beacon or indicator bank unit type	3 illuminated units
Material	PC (UL94 V-2): globe
Mounting diameter	60 Mm
Component name	XVG
Device mounting	Tube mounting with foldable bracket
Light source	LED steady
Light block color	Red/Orange/Green
Indicator bank base type	Base with integrated buzzer

Complementary

[Us] rated supply voltage	220...240 V AC
Cable cross section	0.33 Mm²
Discrete output type	PNP
[Uimp] rated impulse withstand voltage	4.0 KV
Current consumption	68 mA
Noise level	85 DB
Power consumption in VA	10.7 VA
Fundamental frequency	2.64 KHz
Net weight	0.46 Kg

Environment

Product certifications	CE[RETURN]CCC[RETURN]EAC
Ambient air temperature for storage	-20…65 °C
Ambient air temperature for operation	0…50 °C
Electrical shock protection class	Class II
Overvoltage category	III conforming to IEC 60947-5-1
IP degree of protection	IP40

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.500 Cm
Package 1 Width	13.500 Cm
Package 1 Length	56.500 Cm
Package 1 Weight	700.000 G
Unit Type of Package 2	S04
Number of Units in Package 2	8
Package 2 Height	30 Cm
Package 2 Width	40 Cm
Package 2 Length	60 Cm
Package 2 Weight	6.400 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	30
Package 3 Height	71.000 Cm
Package 3 Width	60.000 Cm
Package 3 Length	80.000 Cm
Package 3 Weight	33.000 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised