Product data sheet
Characteristics

XVMM1RAG
Pre assembled and pre cabled indicator bank, Harmony XVM, without buzzer + 3 illuminated units, 45mm, 230V AC/DC



⚠ End of Commercialisation

Commercial status
End of Commercialisation : JUN 30, 2026

Main

Range of product	Harmony XVM
Product or component type	Pre-assembled and pre-cabled indicator bank
Beacon or indicator bank unit type	3 illuminated units
Component name	XVM
Light source	Orange incandescent bulb with BA 15d base steady signalling <5 W Green incandescent bulb with BA 15d base steady signalling <5 W Red incandescent bulb with BA 15d base steady signalling <5 W
Light block color	Red/Orange/Green
[Us] rated supply voltage	230 V AC/DC
Indicator bank base type	Base without buzzer
Mounting mode	Vertical

Complementary

Kit composition	Base unit Aluminium support tube Cover Plastic fixing plate
Mounting diameter	45 Mm
Connections - terminals	Flying leads,clamping capacity: 1 x 0.325 mm² (22 AWG)
Marking	CE
Mounting support	Aluminium tube
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1
Nominal voltage limit	0.85...1.1 Un conforming to IEC 60947-5-1
[Uimp] rated impulse withstand voltage	4 KV conforming to IEC 60947-1
Net weight	0.493 Kg

Environment

IP degree of protection	IP42 vertical position conforming to IEC 60529
Product certifications	CCC
Standards	IEC 60947-1 IEC 60947-5-1
Ambient air temperature for storage	-25…70 °C
Ambient air temperature for operation	-10…50 °C

Overvoltage category	Class I conforming to IEC 60947-1 Class I conforming to IEC 60947-5-1 Class I conforming to IEC 61140
Protective treatment	TC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 Cm
Package 1 Width	8.300 Cm
Package 1 Length	54.000 Cm
Package 1 Weight	545.000 G
Unit Type of Package 2	S04
Number of Units in Package 2	20
Package 2 Height	30.000 Cm
Package 2 Width	40.000 Cm
Package 2 Length	60.000 Cm
Package 2 Weight	12.152 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	Yes
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	6797f094-b2bf-48a4-981a-58794615fad0
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : End of commercialisation

XVMM1RAG is replaced by the following product range:



281190363

⌀40mm Modular Tower Lights

Substitution date: |