Product data sheet
Characteristics

XVS14MMW
Multisound siren, Harmony XVS, prewired, white colour, 0...105dB, 43tones, 240V AC



Main

Range of Product	Harmony XVS
Product or Component Type	Multisound siren
Device short name	XVS

Complementary

Color	White
Material	PC (polycarbonate): back cover PC (polycarbonate)/ABS (acrylonitrile butadiene-styrene): front PC (polycarbonate)/ABS (acrylonitrile butadiene-styrene): back
Net Weight	2.6 Lb(US) (1.2 kg)
Marking	CE
Mounting Support	Bracket
Fixing Mode	3 holes Ø 9 mm
[Uimp] rated impulse withstand voltage	4 KV
Current consumption	50 mA 240 V
Electrical connection	Cable 0.3…0.3 in (6.5…8.5 mm), 0.0005 in² (0.33 mm²) / 22 AWG signalling circuit) Cable 0.3…0.3 in (6.5…8.5 mm), 0.0008 in² (0.52 mm²) / 20 AWG power circuit)
Width	5.5 In (140 mm)
Height	4.5 In (114 mm)
Depth	8.8 In (223 mm)

Environment

Signalling type	43 tones siren
Standards	IEC 61000-6-3 IEC 60947-5-1 EN 60947-01 IEC 61000-6-2
Product Certifications	UL
Protective treatment	TC
Ambient Air Temperature for Storage	-31…158 °F (-35…70 °C)
Ambient Air Temperature for Operation	14…122 °F (-10…50 °C)
Overvoltage category	Class II conforming to IEC 61140
IP degree of protection	IP53 conforming to IEC 60529
[Us] rated supply voltage	240 V AC
Noise level	0…105 DB continuous or intermittent tone)1 m

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.1 In (15.5 cm)
Package 1 Width	6.1 In (15.5 cm)
Package 1 Length	10.8 In (27.5 cm)
Package weight(Lbs)	3.42 Lb(US) (1.55 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Height	11.8 In (30.0 cm)
Package 2 Width	15.7 In (40.0 cm)
Package 2 Length	23.6 In (60.0 cm)
Package 2 Weight	23.537 Lb(US) (10.676 kg)

Environmental data

Recyclability potential, in %	18
Total lifecycle Carbon footprint	12 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	9.4063753213
Carbon footprint of the manufacturing phase [A1 to A3]	9 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1919485861
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.5777583548
Carbon footprint of the installation phase [A5]	0.6 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.07922027
Carbon footprint of the use phase [B2, B3, B4, B6]	0.1 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	2.1045758355
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint (kg CO2 eq, Total Life cycle)	12
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Circularity Profile	End Of Life Information
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised