Product data sheet
Characteristics

XVUC68
Modular tower light, Harmony XVU, illuminated LED units, yellow, 60mm, high flashing, IP65, 24V AC DC



Main

Range of product	Harmony XVU
Product or component type	Modular tower light
Beacon or indicator bank unit type	LED unit
Mounting diameter	60 Mm
Component name	XVU
Light source	LED, yellow
Device application	Automotive Packaging machine Machine tools

Complementary

Signalling type	High flashing
Assembly style	Customer assembly, up to 3 units
Material	PC (polycarbonate) V-2 conforming to UL 94
[Us] rated supply voltage	24 V AC/DC
Maximum power dissipation in W	2.8 W
Current consumption	<= 150 mA
Signalling type	High flashing
Length	60 Mm
Net weight	0.085 Kg

Environment

Product certifications	UL[RETURN]CSA[RETURN]CE[RETURN]EAC[RETURN]RCM[RETURN]CCC
Ambient air temperature for storage	-40…70 °C
IP degree of protection	IP65
Ambient air temperature for operation	-25…50 °C
Vibration resistance	2 gn

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.2 Cm
Package 1 Width	9.2 Cm
Package 1 Length	13.3 Cm
Package 1 Weight	163.0 G
Unit Type of Package 2	S03

Number of Units in Package 2	24
Package 2 Height	30 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	4.759 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	192
Package 3 Height	75 Cm
Package 3 Width	40 Cm
Package 3 Length	80 Cm
Package 3 Weight	31.296 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	Yes
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	C06fce4f-aea2-46a5-aadb-0b38d1efbe3f
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
End of life manual availability	End Of Life Information
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : End of commerc. announced

XVUC68 is replaced by the following product range:



281190286

Harmony XV6 ⌀60mm Modular Tower Lights

Substitution date: |