
Product data sheet
Characteristics

ZARB11WSP
Base station, Harmony pocket remote, 11 relays outputs, pre-wired, 1.5m cable, 12...24V DC



Main

Range of product	Harmony Pocket Remote
Product or component type	Base station
Device short name	ZARB

Complementary

Cable entry	Cable pre-wired
Material	ABS + PC
[Us] rated supply voltage	12...24 V DC
Provided equipment	Internal antenna
Number of relays	11
Relay type	Motion relay outputs with 11 C/O contact Auxiliary relay outputs
Maximum switching current	10 A
Maximum switching voltage	240 V AC (+/- 20 %)
Communication network type	Wireless
Maximum power consumption in VA	12 VA DC at 30 mA (maximum) active relays 24 VA DC at 20 mA (maximum) active relays
Transmission frequency	2.4 GHz
Maximum sensing distance	300 M in free field
Fixing mode	4 holes
Electrical durability	100000 Cycles
Mechanical durability	10000000 Cycles
Width	120 Mm
Height	117 Mm
Depth	51 Mm
Net weight	0.40 Kg

Environment

IP degree of protection	IP66
Radio agreement	FCC IC
Relative humidity	0…97 %
Ambient air temperature for operation	-20…55 °C
Ambient air temperature for storage	-40…70 °C
Product certifications	CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.500 Cm
Package 1 Width	19.000 Cm
Package 1 Length	22.500 Cm
Package 1 Weight	995.000 G
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	30 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	7.477 Kg

Offer Sustainability

Recyclability potential, in %	6
Total lifecycle Carbon footprint	1 117 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	30.0188976378
Carbon footprint of the manufacturing phase [A1 to A3]	30 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1176897638
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2401653543
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1086.2003527494
Carbon footprint of the use phase [B2, B3, B4, B6]	1 086 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.6093188976
Carbon footprint of the end-of-life phase [C1 to C4]	0.6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1117
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	6e438e59-42d1-4633-bfe2-cb5ef607659b
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is know
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised