Product data sheet
Characteristics

ZB2BD2C
Selector switch head, Harmony XB2, metal, black, 22mm, 2 positions, stay put



Main

Range of product	Harmony XB2
Product or component type	Head for selector switch
Component name	ZB2
Bezel material	Chromium plated metal
Device presentation	Basic element
Product compatibility	ZB2..C
Device short name	XB2
Head type	Standard

Complementary

Net weight	0.045 Kg
Mounting diameter	22.5 Mm
Height	29 Mm
Width	29 Mm
Depth	41 Mm
Operator position information	2 positions
Shape of signaling unit head	Round
Operator profile	Black
Type of operator	Stay put
Cap/operator or lens colour	Black
Marking	Unmarked
Mounting location	Front of enclosure
Sale per indivisible quantity	1
Customizable	No
Operator profile	Standard handle
Type of operator	Stay put

Environment

Standards	IEC 60947-5-1 IEC 60947-5-4 IEC 60947-1 GB/T 14048.1 GB/T 14048.5
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…70 °C
Vibration resistance	5 gn (f= 2…500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27

Protective treatment	TC/TH
IP degree of protection	IP65
IK degree of protection	IK06
Product certifications	CE[RETURN]CCC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.9 Cm
Package 1 Width	2.9 Cm
Package 1 Length	4.47 Cm
Package 1 Weight	44.7 G
Unit Type of Package 2	S02
Number of Units in Package 2	150
Package 2 Height	15 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	7 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	3000
Package 3 Height	90 Cm
Package 3 Width	60 Cm
Package 3 Length	80 Cm
Package 3 Weight	139.62 Kg

Offer Sustainability

Recyclability potential, in %	84
Total lifecycle Carbon footprint	0.5 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.3406562107
Carbon footprint of the manufacturing phase [A1 to A3]	0.3 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.0237813741
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.000098248
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.107610109
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	9e63340a-2371-4381-8f9a-5fba0ff349a4
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status :	Commercialised