Product data sheet
Characteristics

LV848382
M2C programmable contacts, MasterPact MTZ2/MTZ3 drawout, 2 contacts, 3A/250VAC



Main

Range	MasterPact
Device short name	M2c
Product or component type	Programmable contact
Device application	Safety logic controller
Range compatibility	MasterPact MTZ2 circuit-breaker MasterPact MTZ3 circuit-breaker
Number of contacts	2
Signal contacts composition	2 NO

Complementary

Mounting mode	Drawout
[Ie] rated operational current	3 A at 250 V AC 3 A at 30 V DC
Minimum load	10 MA at 5 V DC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 Cm
Package 1 Width	6.0 Cm
Package 1 Length	8.2 Cm
Package 1 Weight	70.0 G

Offer Sustainability

Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	7ad12b2f-38d8-4da7-8519-e4f93e0ce077
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, w
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status :	Commercialised