Product data sheet
Characteristics

LVS04012
Distribution block, LINERGY FM, 2P, 200A, 24M, 24holes



Main

Range	Linergy
Range of product	Linergy
Product or component type	Device feeder
Product name	Linergy FM
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure PrismaSeT Prisma PH enclosure
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Mounting support	Slotted backplate DIN rail Plain backplate
Mounting mode	By screws Clip-on
Installed device	Modular device
Poles description	1P + N
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 KV
[Ie] rated operational current	200 A
[In] rated current	200 A at 40 °C
[Ipk] rated peak withstand current	20 KA
Connections - terminals	Supply: crimped lug70 mm² Supply: flexible bars, 20 x 3 mm Distribution: quick-connect terminal strips (phase) , 12 x 4…10 mm² (flexible) Distribution: quick-connect terminal strips (phase) , 12 x 4…10 mm² (rigid) Distribution: quick-connect terminal strips (neutral) , 18 x 4…10 mm² (flexible) Distribution: quick-connect terminal strips (neutral) , 18 x 4…10 mm² (rigid)
9 mm pitches	48
Total number of 18 mm modules	24
Net weight	1.02 Kg
Colour	Anthracite grey (RAL 7016)

Environment

Standards	IEC 61439-1, inside enclosure IEC 61439-2, inside enclosure IEC 60947-7-1
Product certifications	ASTA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.800 Cm
Package 1 Width	5.500 Cm
Package 1 Length	44.500 Cm
Package 1 Weight	983.000 G
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Height	6.800 Cm
Package 2 Width	27.800 Cm
Package 2 Length	44.500 Cm
Package 2 Weight	4.970 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	99.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	261.000 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and cons
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised