Product data sheet
Characteristics

NSYS3X10830
Wall mounted enclosure, PanelSeT S3X, stainless steel 304L, plain door, 1000x800x300mm, IP66



Main

Range	Spacial
Product name	Spacial S3X
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	1000 Mm
Enclosure nominal width	800 Mm
Enclosure nominal depth	300 Mm
Installation accessory type	Wall-mounting
Device composition	1 body 1 reinforcement frame drilled: door 1 door 2 lock: door

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail
Door type	Plain
Number of doors	Front face: 1 door(s)
Door opening side	Reversible (120 °)
Lock type	2 points lock, 3 mm double-bar
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Body and door: stainless steel 304L Lock: zamak Hinge: stainless steel
Surface finish	Body and door: Scotch-Brite® brushed Lock: chromium plated
Net weight	37.4 Kg

Environment

Standards	IEC 62208 UL CUL
Product certifications	UL 508 type A[RETURN]CAN/CSA 22
IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Environmental characteristic	Corrosive Specific hygiene

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	32.000 Cm
Package 1 Width	82.000 Cm
Package 1 Length	103.000 Cm
Package 1 Weight	37.400 Kg
Unit Type of Package 2	PAM
Number of Units in Package 2	6
Package 2 Height	178.000 Cm
Package 2 Width	100.000 Cm
Package 2 Length	120.000 Cm
Package 2 Weight	236.000 Kg

Offer Sustainability

Total lifecycle Carbon footprint	556 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	381.67831462990495
Carbon footprint of the manufacturing phase [A1 to A3]	382 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	74.25106836714137
Carbon footprint of the distribution phase [A4]	74 kg CO2 eq.
Carbon footprint of the installation phase [A5]	1.8564618586720794
Carbon footprint of the installation phase [A5]	2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	98.17616939185503
Carbon footprint of the end-of-life phase [C1 to C4]	98 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	556
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	E893f0a0-d2cc-4011-9425-3873dde70142
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compou
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status :	Commercialised