# Product data sheet
## Characteristics

# NSYS3X4315
Wall mounted enclosure, PanelSeT S3X, stainless steel 304L, plain door, 400x300x150mm, IP66



## Main

| | |
|---|---|
| Range | Spacial |
| Product name | Spacial S3X |
| Device application | Multi-purpose |
| Product or component type | Compact enclosure |
| Enclosure nominal height | 400 Mm |
| Enclosure nominal width | 300 Mm |
| Enclosure nominal depth | 150 Mm |
| Installation accessory type | Wall-mounting |
| Device composition | 1 body<br>1 lock: door<br>1 door |

## Complementary

| | |
|---|---|
| Body type | Single piece body, cross-shaped structure<br>Gutter shaped front rail |
| Door type | Plain |
| Number of doors | Front face: 1 door(s) |
| Door opening side | Reversible (120 °) |
| Lock type | 3 mm double-bar lock |
| Mounting plate description | Without mounting plate |
| Type of gland plate | Without gland plate |
| Accessibility for operation | Front |
| Removable parts | Door by hinges |
| Material | Body and door: stainless steel 304L<br>Lock: zamak<br>Hinge: stainless steel |
| Surface finish | Body and door: Scotch-Brite® brushed<br>Lock: chromium plated |
| Net weight | 5 Kg |

## Environment

| | |
|---|---|
| Standards | IEC 62208<br>UL<br>CUL |
| Product certifications | UL 508 type A[RETURN]CAN/CSA 22 |
| IP degree of protection | IP66 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |
| Environmental characteristic | Corrosive<br>Specific hygiene |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 17.000 Cm |
| Package 1 Width | 31.500 Cm |
| Package 1 Length | 42.000 Cm |
| Package 1 Weight | 4.900 Kg |
| Unit Type of Package 2 | PAM |
| Number of Units in Package 2 | 78 |
| Package 2 Height | 182.000 Cm |
| Package 2 Width | 100.000 Cm |
| Package 2 Length | 120.000 Cm |
| Package 2 Weight | 396.200 Kg |

## Offer Sustainability

| | |
|---|---|
| Total lifecycle Carbon footprint | 73 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 50.00598239803568 |
| Carbon footprint of the manufacturing phase [A1 to A3] | 50 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 9.728081149705687 |
| Carbon footprint of the distribution phase [A4] | 10 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.24322628629660933 |
| Carbon footprint of the installation phase [A5] | 0.2 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 0 |
| REACh free of SVHC | Yes |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 0 kg CO2 eq. |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| Sustainable packaging | No |
| Carbon footprint of the end-of-life phase [C1 to C4] | 12.862653209093306 |
| Carbon footprint of the end-of-life phase [C1 to C4] | 13 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |
| Total lifecycle Carbon footprint | 73 |
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| SCIP Number | E893f0a0-d2cc-4011-9425-3873dde70142 |
| REACh Regulation | Free of Substances of Very High Concern above the threshold |
| EU RoHS Directive | Compliant |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Cadmium and cadmium compou |
| PVC free | Yes |
| Silicone-free | Yes |
| End of life manual availability | No need of specific recycling operations |
| Take-back | No |

## Contractual warranty

| | |
|---|---|
| Warranty (in months) | 18 |

| | |
|---|---|
| Product Life Status : | Commercialised |