Product data sheet
Characteristics

NSYS3X8625
Wall mounted enclosure, PanelSeT S3X, stainless steel 304L, plain door, 800x600x250mm, IP66



Main

Range	Spacial
Product name	Spacial S3X
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	800 Mm
Enclosure nominal width	600 Mm
Enclosure nominal depth	250 Mm
Installation accessory type	Wall-mounting
Device composition	1 body 1 door 2 lock: door 2 perforated vertical profile drilled: door

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail
Door type	Plain
Number of doors	Front face: 1 door(s)
Door opening side	Reversible (120 °)
Lock type	2 points lock, 3 mm double-bar
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Body and door: stainless steel 304L Lock: zamak Hinge: stainless steel
Surface finish	Body and door: Scotch-Brite® brushed Lock: chromium plated
Net weight	22.474 Kg

Environment

Standards	IEC 62208 UL CUL
Product certifications	CAN/CSA 22[RETURN]UL 508 type A
IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Environmental characteristic	Specific hygiene Corrosive

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.000 Cm
Package 1 Width	61.500 Cm
Package 1 Length	82.000 Cm
Package 1 Weight	20.000 Kg
Unit Type of Package 2	PAM
Number of Units in Package 2	12
Package 2 Height	196.000 Cm
Package 2 Width	100.000 Cm
Package 2 Length	120.000 Cm
Package 2 Weight	253.000 Kg

Offer Sustainability

Total lifecycle Carbon footprint	297 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	204.10605060422722
Carbon footprint of the manufacturing phase [A1 to A3]	204 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	39.706453672268104
Carbon footprint of the distribution phase [A4]	40 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.9927603522310584
Carbon footprint of the installation phase [A5]	1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	52.50062534323797
Carbon footprint of the end-of-life phase [C1 to C4]	53 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	297
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	E893f0a0-d2cc-4011-9425-3873dde70142
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compou
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status :	Commercialised