Product data sheet
Characteristics

NSYZZ253G
Polyester glassreinf. plinth for encl. PLAZ(T)53 front opening IP44-IK10 RAL7035



Main

Range	PanelSeT
Accessory / separate part category	Enclosure accessory
Product or component type	Plinth
Device application	Multi-purpose
Enclosure nominal dimensions	-
Device composition	Fixing elements 2 front panel 2 side part
Range compatibility	PanelSeT PLA

Complementary

Fixing mode	By screws - on side parts location
Colour	Plinth: grey (RAL 7035)
Height	200 Mm
Width	535 Mm
Depth	310 Mm

Environment

IP degree of protection	IP44
IK degree of protection	IK10

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.000 Cm
Package 1 Width	44.000 Cm
Package 1 Length	64.000 Cm
Package 1 Weight	5.968 Kg
Unit Type of Package 2	PAM
Number of Units in Package 2	20
Package 2 Height	76.000 Cm
Package 2 Width	100.000 Cm
Package 2 Length	120.000 Cm
Package 2 Weight	132.000 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	No
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	1341ad4e-77b9-40e3-bab0-32043fbc5959
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised