SIEMENS

Data sheet 3NP1153-1BC10



SENTRON, Fuse switch disconnector 3NP1, 3-pole, NH2, 400 A, for Busbar system 8US 60 mm, flat terminal, Cover level 32/70 mm

Model	
product designation	Fuse switch disconnector
busbar design	busbar thickness 5 or 10 mm
design of the safety monitoring	Without
design of the load switch strip form	No
type of the driving mechanism motor drive	No
General technical data	
number of poles	3
type of device	For 60 mm 8US busbar system
size of disconnecting link	2 and 1
size of fuse link	NH1, NH2
let-through current with closed switch maximum	40 kA
mechanical service life (operating cycles) typical	1 000
I2t value with closed switch maximum	2 150 kA²·s
power factor	
● at AC-22 B	0.65
● at AC-23 B	0.35
● with capacitive load	-0.25
fuse system	LV HRC fuse
degree of pollution	3
Voltage	
insulation voltage	
● rated value	690 V
● with degree of pollution 3 at AC rated value	690 V
● with degree of pollution 2 at AC rated value	1 000 V
power factor at AC-21 B	0.95
surge voltage resistance rated value	8 kV
● operational current	
— at 35 °C rated value	400 A
— at 40 °C rated value	400 A
— at 45 °C rated value	392 A
— at 50 °C rated value	372 A
— at 55 °C rated value	356 A
● operational current	
— at AC-21 B at 240 V rated value	400 A
— at AC-21 B at 400 V rated value	400 A
— at AC-21 B at 500 V rated value	400 A
— at AC-21 B at 690 V rated value	400 A

Subject to change without notice
© Copyright Siemens

— at AC-22 B at 240 V rated value	400 A
— at AC-22 B at 400 V rated value	400 A
— at AC-22 B at 500 V rated value	400 A
— at AC-22 B at 690 V rated value	400 A
— at AC-23 B at 690 V rated value	125 A
— at AC-23 B at 500 V rated value	315 A
— at AC-23 B at 400 V rated value	400 A
— at AC-23 B at 240 V rated value	400 A
— at DC-21 B at 120 V rated value	400 A
— at DC-21 B at 240 V rated value	400 A
— at DC-21 B at 440 V rated value	400 A
— at DC-22 B at 120 V rated value	400 A
— at DC-22 B at 240 V rated value	400 A
— at DC-22 B at 440 V rated value	315 A
— at DC-23 B at 120 V rated value	250 A
— at DC-23 B at 240 V rated value	250 A
— at DC-23 B at 440 V rated value	160 A
let-through current with high-speed activation maximum	40 kA
operating voltage	
● at AC rated value maximum	690 V
● at DC rated value	440 V
● at DC rated value maximum	440 V
Protection class	
protection class IP	
● with closed switch with cover or cable lug cover	IP40
● with closed switch without cover or cable lug cover	IP30
● open	IP20
Dissipation	
power loss [W]	
● with conventional rated thermal current without fuse per pole	14 W
● with conventional rated thermal current without fuse per device	42 W
● for rated value of the current at AC in hot operating state per pole	16.8 W
● of the fuse per fuse maximum	34 W
Main circuit	
operational current	
● rated value	400 A
● with capacitive load at 400 V rated value	72 A
● with capacitive load at 500 V rated value	55 A
Auxiliary circuit	
number of CO contacts for auxiliary contacts	0
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
Suitability	
suitability for use main switch	No
suitability for use switch disconnector	Yes
suitability for use EMERGENCY OFF switch	No
suitability for use maintenance/repair switch	Yes
Product details	
product function phase failure monitoring	No
product component	
● undervoltage release	No
● undervoltage release with leading contact	No
product feature sealable	Yes
product extension auxiliary switch	Yes
product extension optional locking capability	Yes
product extension optional phase failure monitoring	Yes

Subject to change without notice
© Copyright Siemens

product extension optional fuse monitoring	Yes
product extension optional voltage trigger	No
product extension optional overvoltage protection monitoring	Yes
Product function	
product function overvoltage protection monitoring	No
Short circuit	
conditional short-circuit current (Iq)	
• at AC at 240 V with high-speed activation rated value	80 kA
• at AC at 500 V with high-speed activation rated value	80 kA
• at AC at 690 V with high-speed activation rated value	50 kA
• with closed switch at AC at 240 V rated value	100 kA
• with closed switch at AC at 500 V rated value	100 kA
• with closed switch at AC at 690 V rated value	100 kA
Connections	
arrangement of electrical connectors for main current circuit	other
connectable conductor cross-section for main contacts	
• solid or stranded minimum	25 mm²
• solid or stranded maximum	240 mm²
• stranded minimum	25 mm²
• stranded maximum	240 mm²
tightening torque with screw-type terminals	
• minimum	10 N·m
• maximum	12 N·m
type of connectable conductor cross-sections of the laminated conductors maximum	34 x 18 mm
type of connection technology	Flat terminal
Mechanical Design	
height	306 mm
width	209.4 mm
width of the busbar	
• minimum	12 mm
• maximum	30 mm
depth	157 mm
fastening method	busbar
fastening method	
• floor mounting	No
• rail mounting	Yes
mounting position	horizontal/vertical
busbar center-to-center spacing	60 mm
Net Weight	4.287 kg
Environmental conditions	
ambient temperature during operation	
• minimum	-25 °C
• maximum	55 °C
ambient temperature during storage	
• minimum	-50 °C
• maximum	80 °C
Certificates	
reference code according to IEC 81346-2	Q
Approvals Certificates	

Environment		General Product Approval			Miscellaneous
Environmental Confirmations	Environmental Confirmations	CCC	cULus	VDE	


Subject to change without notice
© Copyright Siemens

General Product Approval	Test Certificates		Maritime application
	Type Test Certific-ates/Test Report	Special Test Certific-ate	


Maritime application	other
	Confirmation

Further information


Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NP1153-1BC10
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3NP1153-1BC10
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NP1153-1BC10
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications
Kennlinien
https://curves.simaris.siemens.com/curves/3NP1153-1BC10



Subject to change without notice
© Copyright Siemens



Subject to change without notice
© Copyright Siemens



last modified: 3/29/2026

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens