SIEMENS

## Data sheet 3RU6116-1CB0




Overload relay 1.8...2.5 A size S00, class 10, for motor protection for mounting onto contactors main circuit: screw terminal AUX. circuit: screw terminal manual automatic reset

| | |
|---|---|
| **product brand name** | SIRIUS |
| **product designation** | Thermal overload relay |
| **product type designation** | 3RU6 |
| **General technical data** | |
| **size of contactor can be combined company-specific** | S00 |
| **power loss [W] total typical** | 5.1 W |
| power loss [W] for rated value of the current at AC in hot operating state | 5.7 W |
| ● per pole | 1.9 W |
| **type of calculation of power loss current-dependent** | quadratic |
| insulation voltage with degree of pollution 3 at AC rated value | 690 V |
| **surge voltage resistance rated value** | 6 kV |
| **shock resistance according to IEC 60068-2-27** | 8 g / 11 ms |
| **Substance Prohibitance (day/month/year)** | 05/01/2012 |
| **Net Weight** | 0.13 kg |
| **Ambient conditions** | |
| installation altitude at height above sea level maximum | 2 000 m |
| **ambient temperature** | |
| ● during operation | -40 ... +70 °C |
| ● during transport | -55 ... +80 °C |
| relative humidity during operation | 0 ... 90 % |
| **Main circuit** | |
| **number of poles for main current circuit** | 3 |
| **adjustable current response value current of the current-dependent overload release** | 1.8 ... 2.5 A |
| operating voltage rated value | 690 V |
| **operating frequency rated value** | 50 ... 60 Hz |
| **operational current rated value** | 2.5 A |
| **Auxiliary circuit** | |
| **operational current of auxiliary contacts at AC-15** | |
| ● at 24 V | 3 A |
| ● at 230 V | 2 A |
| **operational current of auxiliary contacts at DC-13** | |
| ● at 24 V | 2 A |
| ● at 110 V | 0.22 A |
| **Protective and monitoring functions** | |
| **trip class** | CLASS 10 |
| **design of the overload release** | thermal |
| **Installation/ mounting/ dimensions** | |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| **mounting position** | any |
| **fastening method** | Contactor mounting |
| **height** | 76 mm |
| **width** | 45 mm |
| **depth** | 70 mm |
| required spacing for grounded parts at the side | 6 mm |
| **Connections/ Terminals** | |
| **type of electrical connection** | |
| ● for main current circuit | screw-type terminals |
| ● for auxiliary and control circuit | screw-type terminals |
| **arrangement of electrical connectors for main current circuit** | Top and bottom |
| type of connectable conductor cross-sections for main contacts | |
| ● solid or stranded | 2x (0,5 ... 1,5 mm²), 2x (0,75 ... 2,5 mm²), 2x 4 mm² |
| ● finely stranded with core end processing | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²) |
| **type of connectable conductor cross-sections** | |
| ● for auxiliary contacts | |
| — solid or stranded | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²) |
| — finely stranded with core end processing | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²) |
| ● for AWG cables for auxiliary contacts | 2x (20 ... 16), 2x (18 ... 14) |
| tightening torque for main contacts with screw-type terminals | 0.8 ... 1.2 N·m |
| Electrical Safety | |
| **protection class IP on the front according to IEC 60529** | IP20 |
| **touch protection on the front according to IEC 60529** | finger-safe, for vertical contact from the front |

**Approvals Certificates**


| General Product Approval | | | | Maritime application | other |
|---|---|---|---|---|---|
| CCC | cULus | EAC | CE EG-Konf. | CCS (China Classification Society) | Confirmation |


| other | Environment |
|---|---|
| 产品合格 QC PASS | Environmental Confirmations |

**Further information**

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/products?pnid=16027&lc=en-CN



© Copyright Siemens





Subject to change without notice
© Copyright Siemens




**last modified:** 4/4/2026


Subject to change without notice
© Copyright Siemens