SIEMENS

Data sheet 3VA2716-6AC11-0AA0

fixed-mounted molded case circuit breaker w. handle frame 1600; 4AUX and trip alarm switch S24; Icu "H" Icu=85kA @ 415V, 4-pole, left ETU350, LSI, In=1600A rotary coding switch Ir=640...1600A Isd=1...10xIn, Ii=1.5...15xIn N conductor protec. adjustable OFF, 50%, 100%, 200% rear vertical connection No communication connection, no measurement function Without additional alarm switch assembly With mechanical calling without 2nd auxiliary release without 1st auxiliary release

Model	
product designation	Molded case circuit breaker
design of the product	MCCB
design of the actuating element	toggel handle actuator
type of the driving mechanism	manual operating mechanism
type of the driving mechanism / motor drive	No
design of the overcurrent release	ETU350
General technical data	
number of poles	4
mechanical service life (operating cycles) / typical	10 000
electrical endurance (operating cycles) / at AC-1 / at 380/415 V	2 000
insulation voltage / rated value	1 000 V
operational current	
● at 45 °C / rated value	1 600 A
continuous current / rated value / maximum	1 600 A
Supply voltage	
operating voltage	
● at AC / at 50/60 Hz / rated value	690 V
Protection class	
protection class IP / on the front	IP20
Breaking Capacity	
switching capacity class of the circuit breaker	H
power loss [W]	
● for rated value of the current / at AC / in hot operating state / per pole	77 W
● maximum	231 W
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	4
Suitability	
suitability for use	system protection
Adjustable parameters	
adjustable current response value current / of the short-time delayed short-circuit release	
● initial value	1 600 A
● full-scale value	16 000 A
adjustable current response value current / of the current-dependent overload release / initial value	640 A
Product details	
product component	
● trip indicator	Yes
● voltage trigger	No
● undervoltage release	No
product extension / optional / motor drive	No
Product function	
product function	
● grounding protection	No

Subject to change without notice
© Copyright Siemens

● communication function	No
Display and operation	
display version	Without display
Short circuit	
operating short-circuit current breaking capacity (Ics)	
● at 240 V / rated value	150 kA
● at 415 V / rated value	85 kA
● at 440 V / rated value	85 kA
● at 500 V / rated value	55 kA
● at 690 V / rated value	36 kA
maximum short-circuit current breaking capacity (Icu)	
● at 240 V / rated value	150 kA
● at 415 V / rated value	85 kA
● at 440 V / rated value	85 kA
● at 500 V / rated value	55 kA
● at 690 V / rated value	36 kA
short-circuit current making capacity (Icm)	
● at 240 V / rated value	330 kA
● at 415 V / rated value	187 kA
● at 440 V / rated value	187 kA
● at 500 V / rated value	121 kA
● at 690 V / rated value	76 kA
Connections	
arrangement of electrical connectors / for main current circuit	Main connection rear vertical
type of electrical connection / for main current circuit	busbar connection
Mechanical Design	
height	296 mm
width	280 mm
depth	183 mm
fastening method	fixed mounting
Net Weight	17.106 kg
Environmental conditions	
ambient temperature / during operation	
● minimum	-25 °C
● maximum	70 °C
ambient temperature / during storage	
● minimum	-40 °C
● maximum	70 °C
Further information	

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2716-6AC11-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VA2716-6AC11-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2716-6AC11-0AA0
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications
Kennlinien
https://curves.simaris.siemens.com/curves/3VA2716-6AC11-0AA0

Subject to change without notice
© Copyright Siemens



last modified:	11/24/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens