SIEMENS

## Data sheet 6GK5008-0GA10-1AB2



SCALANCE XB008G unmanaged Industrial Ethernet Switch for 10/100/1000 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V DC power supply, with 8x 10/100/1000 Mbit/s RJ45 ports electrical Manual available as a download .

| | |
|---|---|
| **product type designation** | |
| product brand name | SCALANCE |
| product type designation | XB008G |
| Technical Product Detail Page | https://i.siemens.com/1P6GK5008-0GA10-1AB2 |
| **transfer rate** | |
| transfer rate | 10, 100, 1000 Mbit/s |
| **interfaces / for communication / integrated** | |
| number of electrical connections | |
| ● for network components or terminal equipment | 8; RJ45 |
| number of 100 Mbit/s SC ports | |
| ● for multimode | 0 |
| **interfaces / other** | |
| number of electrical connections | |
| ● for power supply | 1 |
| type of electrical connection | |
| ● for power supply | 3-pole terminal block |
| **supply voltage, current consumption, power loss** | |
| **type of voltage / 1 / of the supply voltage** | DC |
| ● supply voltage / 1 / rated value | 24 V |
| ● power loss [W] / 1 / rated value | 12.5 W |
| ● supply voltage / 1 / voltage range | 19.2 ... 28.8 |
| ● consumed current / 1 / maximum | 0.52 A |
| ● type of electrical connection / 1 / for power supply | 3-pole terminal block |
| ● product component / 1 / fusing at power supply input | Yes |
| ● fuse protection type / 1 / at input for supply voltage | 0,6 A / 60 V |
| **ambient conditions** | |
| ambient temperature | |
| ● during operation | -10 ... +60 °C |
| ● during storage | -40 ... +80 °C |
| ● during transport | -40 ... +80 °C |
| relative humidity | |
| ● at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP20 |
| **design, dimensions and weights** | |
| design | Box |
| width | 45 mm |
| height | 100 mm |
| depth | 87 mm |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| net weight | 0.188 kg |
| fastening method | |
| ● 35 mm DIN-rail mounting | Yes |
| ● wall mounting | Yes |
| ● S7-1500 rail mounting | No |
| **product functions / management, configuration, engineering** | |
| product function | |
| ● multiport mirroring | No |
| ● CoS | Yes |
| ● switch-managed | No |
| PROFINET conformity class | A |
| **product functions / redundancy** | |
| product function | |
| ● Parallel Redundancy Protocol (PRP)/operation in the PRP-network | Yes |
| ● Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) | No |
| **standards, specifications, approvals** | |
| certificate of suitability | |
| ● CE marking | Yes |
| ● cULus approval | Yes |
| ● KC approval | Yes |
| ● Regulatory Compliance Mark (RCM) | Yes |
| standard | |
| ● for EMC interference emission | EN 61000-6-4 (Class B) |
| ● for immunity to EMC | EN 61000-6-2 |
| ● for safety / from CSA and UL | UL 60950-1, CSA C22.2 No. 60950-1 |
| **standards, specifications, approvals / hazardous environments** | |
| certificate of suitability | |
| ● ATEX | Yes |
| ● UKEX | Yes |
| ● IECEx | Yes |
| ● CCC / for hazardous zone according to GB standard | Yes |
| ● FM registration | Yes |
| **standards, specifications, approvals / other** | |
| certificate of suitability | |
| ● RoHS conformity | Yes |
| resistance to air pollution / conformity according to ANSI/ISA-71.04 | Yes; G3 |
| **standards, specifications, approvals / Environmental Product Declaration** | |
| Environmental Product Declaration | Yes |
| global warming potential [CO2 eq] | |
| ● total | 123.2298 kg |
| ● during manufacturing | 6.94 kg |
| ● during operation | 116 kg |
| ● after end of life | 0.217 kg |
| **product functions / general** | |
| MTBF | 112 a |
| warranty period | 5 a |
| product function / is supported / identification link | Yes; acc. to IEC 61406-1:2022 |
| **further information / internet links** | |
| internet link | |
| ● to website: Selection guide for cables and connectors | https://support.industry.siemens.com/cs/ww/en/view/109766358 |
| ● to web page: selection aid TIA Selection Tool | https://www.siemens.com/tstcloud |
| ● to website: Industrial communication | https://www.siemens.com/simatic-net |
| ● to web page: SiePortal | https://sieportal.siemens.com/ |
| ● to website: Image database | https://www.automation.siemens.com/bilddb |
| ● to website: CAx-Download-Manager | https://www.siemens.com/cax |
| ● to website: Industry Online Support | https://support.industry.siemens.com |


Subject to change without notice
© Copyright Siemens

| security information | |
|---|---|
| security information | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7) |

| Approvals / Certificates | |
|---|---|
| Environmental Product Declaration | |
| ● global warming potential [CO2 eq] / during manufacturing | 6.94 kg |
| ● global warming potential [CO2 eq] / during sales | 0.0728 kg |
| ● global warming potential [CO2 eq] / during operation | 116 kg |
| ● global warming potential [CO2 eq] / after end of life | 0.217 kg |
| ● global warming potential [CO2 eq] / total | 123.2298 kg |

**Environment**

**General Product Approval**

Declaration of Conformity

**General Product Approval**

China RoHS

**EMV**

**For use in hazardous locations**

**For use in hazardous locations**

FM

CCC-Ex

**other**

Miscellaneous

**Industrial Communication**

PROFINET

**last modified:** 8/28/2026


© Copyright Siemens