SIEMENS

Data sheet 6ES7541-1AD00-0AB0



Figure similar

spare part SIMATIC S7-1500, CM PTP RS-232 HF communications module for serial connection RS-232, Freeport, 3964 (R), USS, Modbus RTU master, device, 115200 Kbps, 9-pin D-sub plug

General information	
Product type designation	CM PtP RS 232 HF
Product function	
● I&M data	Yes; I&M 0
● Fast startup	Yes
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V12 / V12
● STEP 7 configurable/integrated from version	V5.5 SP2 with GSD file
● PROFIBUS from GSD version/GSD revision	- / -
● PROFINET from GSD version/GSD revision	V2.3 / -
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Input current	
Current consumption (rated value)	50 mA; From the backplane bus
Power	
Power consumption from the backplane bus	0.75 W
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
● Inputs	8 byte
Interface types	
RS 232	
● Transmission rate, max.	115.2 kbit/s
● Cable length, max.	15 m
● RS 232 auxiliary signals	RTS, CTS, DTR, DSR, RI, DCD
Protocols	
Integrated protocols	
Freeport	
— Telegram length, max.	4 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
3964 (R)	
— Telegram length, max.	4 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any

Subject to change without notice
© Copyright Siemens

Modbus RTU master	
— Address area	1 to 247, extended 1 to 65535
— max. number of devices	1
Modbus RTU device	
— Address area	1 to 247, extended 1 to 65535
Telegram buffer	
● Buffer memory for telegrams	8 kbyte
● Number of telegrams which can be buffered	255
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes
● Hardware interrupt	No
Diagnoses	
● Wire break	Yes
Diagnostics indication LED	
● RUN LED	Yes; green LED
● ERROR LED	Yes; red LED
● Receive RxD	Yes; Yellow LED
● Transmit TxD	Yes; Yellow LED
Potential separation	
between backplane bus and interface	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	0 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	0 °C
● vertical installation, max.	40 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200MP system manual
Decentralized operation	
to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1500	Yes
to standard PROFINET controller	Yes
Dimensions	
Width	35 mm
Height	147 mm
Depth	127 mm
Weights	
Weight, approx.	0.22 kg
Classifications	

	Version	Classification
eClass	16	27-24-22-08
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423

Subject to change without notice
© Copyright Siemens

ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration | EG-Konf. | UKCA | UL | KC

General Product Approval | For use in hazardous locations

RCM | EAC | KC | China RoHS | Manufacturer Declaration | IECEx

For use in hazardous locations

FM | UL | FM | CCC-Ex | ATEX | Type Examination Certificate

For use in hazardous locations | Maritime application

IECEx | Miscellaneous | CCC-Ex | ABS | Bureau Veritas | DNV

Maritime application

LRS | RINA | RMRS | CCS (China Classification Society) | KR (Korean Register of Shipping)

last modified: 10/23/2025

Subject to change without notice
© Copyright Siemens