SIEMENS

## Data sheet 3VA2463-5HN42-0AA0



circuit breaker 3VA2 IEC Frame 630 breaking capacity class M Icu=55 kA @ 415 V 4-pole, line protection ETU350, LSI, In=630 A overload protection Ir=250 A...630 A short-circuit protection Isd=1.5...9x Ir, Ii=9x In neutral conductor protection adjustable (OFF, 50%, 100%) nut keeper kit

| | |
|---|---|
| **Model** | |
| product brand name | SENTRON |
| product designation | Molded case circuit breaker |
| design of the product | Line protection |
| design of the overcurrent release | ETU350 |
| protection function of the overcurrent release | LSI |
| number of poles | 4 |
| **General technical data** | |
| insulation voltage / rated value | 800 V |
| operating voltage / at AC / rated value | 690 V |
| power loss [W] / maximum | 162 W |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 54 W |
| mechanical service life (operating cycles) / typical | 20 000 |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V | 5 000 |
| electrical endurance (operating cycles) / at AC-1 / at 690 V | 3 500 |
| product feature / for neutral conductors / upgradable/retrofittable / short-circuit and overload proof | No |
| ground-fault monitoring version | Without |
| product function | |
| ● communication function | No |
| ● other measurement function | No |
| Net Weight | 6.624 kg |
| **Current** | |
| operational current | |
| ● at 40 °C | 630 A |
| ● at 45 °C | 612 A |
| ● at 50 °C | 593 A |
| ● at 55 °C | 575 A |
| ● at 60 °C | 557 A |
| ● at 65 °C | 538 A |
| ● at 70 °C | 520 A |
| **Switching capacity according to IEC 60947** | |
| switching capacity class of the circuit breaker | M |
| maximum short-circuit current breaking capacity (Icu) | |
| ● at 240 V | 85 kA |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| ● at 415 V | 55 kA |
| ● at 440 V | 55 kA |
| ● at 500 V | 36 kA |
| ● at 690 V | 6 kA |
| operating short-circuit current breaking capacity (Ics) | |
| ● at 240 V | 85 kA |
| ● at 415 V | 55 kA |
| ● at 440 V | 55 kA |
| ● at 500 V | 36 kA |
| ● at 690 V | 6 kA |
| short-circuit current making capacity (Icm) | |
| ● at 240 V | 187 kA |
| ● at 415 V | 121 kA |
| ● at 440 V | 121 kA |
| ● at 500 V | 75.6 kA |
| ● at 690 V | 9 kA |
| **Adjustable parameters** | |
| product feature / for L-tripping / can be switched on/off | No |
| adjustable response value setting current (Ir) / of the L-trip / with I2t characteristic | |
| ● minimum | 250 A |
| ● maximum | 630 A |
| adjustable response value delay time (tr) / for L-tripping / with I2t characteristic | |
| ● minimum | 0.5 s |
| ● maximum | 12 s |
| adjustable response value setting current (Isd) / of S-trip / with I2t characteristic | |
| ● minimum | 375 A |
| ● maximum | 5 670 A |
| adjustable response value delay time (tsd) / for S-tripping / with I2t characteristic | |
| ● minimum | 0.0001 s |
| ● maximum | 0.4 s |
| adjustable response value setting current (Ii) / for I-tripping | |
| ● minimum | 5 670 A |
| ● maximum | 5 670 A |
| adjustable setting current (InN) / for N-tripping | |
| ● minimum | 125 A |
| ● maximum | 630 A |
| design of the N-conductor protection | adjustable OFF; 50%; 100% |
| product function / grounding protection | No |
| **Mechanical Design** | |
| product component | |
| ● undervoltage release | No |
| ● voltage trigger | No |
| ● trip indicator | No |
| height [in] | 9.76 in |
| height | 248 mm |
| width [in] | 7.24 in |
| width | 184 mm |
| depth [in] | 4.33 in |
| depth | 110 mm |
| **Connections** | |
| arrangement of electrical connectors / for main current circuit | Front terminal |
| type of electrical connection / for main current circuit | on both sides nut keeper kit |
| type of connectable conductor cross-sections / for flat-bar terminal connection / minimum | 20 x 1 mm |
| type of connectable conductor cross-sections / for flat-bar terminal connection / maximum | 35 x 10 mm |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| design of the surface / of the connections / on the top of the switch (N, 1, 3, 5) | silver |
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6) | silver |
| **Auxiliary circuit** | |
| number of CO contacts / for auxiliary contacts | 0 |
| **Accessories** | |
| product extension / optional / motor drive | Yes |
| **Environmental conditions** | |
| protection class IP / on the front | IP40 |
| ambient temperature | |
| • during operation / minimum | -25 °C |
| • during operation / maximum | 70 °C |
| • during storage / minimum | -40 °C |
| • during storage / maximum | 80 °C |
| **Environmental footprint** | |
| global warming potential [CO2 eq] / total | 495 kg |
| global warming potential [CO2 eq] / during manufacturing | 28.7 kg |
| global warming potential [CO2 eq] / during operation | 470 kg |
| global warming potential [CO2 eq] / after end of life | -4.07 kg |
| Siemens eco profile (SEP) | Siemens EcoTech |
| **reference code / according to IEC 81346-2** | Q |

## Approvals / Certificates

### General Product Approval

CCC VDE Miscellaneous EAC Confirmation

| General Product Approval | EMV | Test Certificates | | |
|---|---|---|---|---|
| UKCA CE EG-Konf. | RCM | Type Test Certificates/Test Report | Special Test Certificate | Miscellaneous |

| Maritime application | | | | other | other |
|---|---|---|---|---|---|
| ABS | BUREAU VERITAS | DNV | LRS | CCS (China Classification Society) | Miscellaneous |

| other | | | Dangerous goods | Environment | |
|---|---|---|---|---|---|
| Miscellaneous | Confirmation | 产品合格 QC PASS | Transport Information | Environmental Confirmations | EPD |

### Environment

Environmental Confirmations Siemens EcoTech

## Further information

**Information on the packaging**


Subject to change without notice
© Copyright Siemens

https://support.industry.siemens.com/cs/ww/en/view/109813875

**Information for data generation and storage**
https://support.industry.siemens.com/cs/ww/en/view/109995012

**Information- and Downloadcenter (Catalogs, Brochures,…)**
https://www.siemens.com/lowvoltage/catalogs

**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2463-5HN42-0AA0


**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/3VA2463-5HN42-0AA0

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2463-5HN42-0AA0

**CAx-Online-Generator**
https://www.siemens.com/cax

**Tender specifications**
https://www.siemens.com/specifications


**Kennlinien**
https://curves.simaris.siemens.com/curves/3VA2463-5HN42-0AA0








Subject to change without notice
© Copyright Siemens




**last modified:** 9/2/2026


Subject to change without notice
© Copyright Siemens

© Copyright Siemens