SIEMENS

Data sheet 6EP3333-3SA00-0AY0

SITOP PSU2200/1AC/24VDC/5A

SITOP PSU2200 STABILIZED POWER SUPPLY PSU2200 INPUT: 100-240 V AC output: 24 V DC/5 A

General information	
Technical Product Detail Page	https://i.siemens.com/1P6EP3333-3SA00-0AY0
product brand name	SITOP
product type designation	PSU2200
product designation	Power supply SITOP PSU2200
type of current supply	24 V/5 A
input	
type of the power supply network	1-phase AC
phase number	1
voltage curve at input	AC
supply voltage at AC	
● minimum rated value	100 V
● maximum rated value	240 V
● initial value	90 V
● full-scale value	264 V
supply voltage	
● at 50 Hz	240 V
● at 60 Hz	120 V
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
wide range input	Yes
buffering time for rated value of the output current in the event of power failure minimum	45 ms
operating condition of the mains buffering	at Vin = 230 V
input current	
● at rated input voltage 115 V	2 A
● at rated input voltage 230 V	1.2 A
current limitation of inrush current at 25 °C maximum	35 A
I2t value maximum	2 A²·s
fuse protection type	internal
fuse protection type in the feeder	Recommended miniature circuit breaker: 16 A characteristic B
output	
voltage curve at output	Controlled, isolated DC voltage
product function output voltage controlled	Yes
product function output voltage stabilized	Yes
output voltage at DC rated value	24 V
output voltage adjustable	Yes; via potentiometer
adjustable output voltage	21.6 ... 26.4 V
relative overall tolerance of the voltage	1 %
relative control precision of the output voltage	
● on slow fluctuation of input voltage	0.5 %
● on slow fluctuation of ohm loading	0.5 %
voltage peak	
● maximum	450 mV
● typical	150 mV
display version for normal operation	Green LED for 24 V OK
behavior of the output voltage when switching on	Overshoot of Vout < 5 %
response delay maximum	500 ms at 115 / 230 V AC

Subject to change without notice
© Copyright Siemens

voltage increase time of the output voltage	
● typical	30 ms
output current	
● rated value	5 A
● rated range	0 ... 5 A; +40 ... +70 °C: Derating 1.67%/K at 115 V AC; +50 ... +70 °C Derating 2.5%/K at 230 V AC
supplied active power typical	120 W
bridging of equipment	No
efficiency	
efficiency in percent	88.5 %
power loss [W]	
● at rated output voltage for rated value of the output current typical	16 W
● during no-load operation maximum	0.15 W
closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	1 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	10 %
protection and monitoring	
design of the overvoltage protection	< 33.6 V (latch mode)
property of the output short-circuit proof	Yes
design of short-circuit protection	constant current characteristic (hiccup mode when Ua < 80%), automatic hot restart when the fault is fixed
design of the current limitation	105-150% of rated load current and Uout > 80%, Constant current limit, Auto recovery
safety	
galvanic isolation between input and output	Yes
galvanic isolation	Output voltage: SELV, ES1 (IEC 62368-1), DVC As (IEC 61204-7)
operating resource protection class	Class I
leakage current	
● maximum	0.5 mA
protection class IP	IP20
EMC	
standard	
● for emitted interference	EN 55032 Class B
● for mains harmonics limitation	EN 61000-3-2
● for interference immunity	EN 55035
standards, specifications, approvals	
certificate of suitability	
● CE marking	Yes
● UL approval	No
● UKCA marking	Yes
● EAC approval	No
● Regulatory Compliance Mark (RCM)	No
● CCC approval	Yes
● NEC Class 2	No
type of certification	
● BIS	No
● CB-certificate	Yes
MTBF at 25 °C	700 000 h; according to SR-332, 100% full load (24 V, 5 A), input voltage: 115 V / 230 V AC
standards, specifications, approvals hazardous environments	
certificate of suitability	
● IECEx	No
● ATEX	No
● ULhazloc approval	No
● FM registration	No
standards, specifications, approvals marine classification	
shipbuilding approval	No

Subject to change without notice
© Copyright Siemens

Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	No
● French marine classification society (BV)	No
● Det Norske Veritas (DNV)	No
● Lloyds Register of Shipping (LRS)	No
ambient conditions	
ambient temperature	
● during operation	-30 ... +70 °C; With natural convection
● during transport	-40 ... +85 °C
● during storage	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 20 ... 90% no condensation
connection method	
type of electrical connection	screw terminal
● at input	L, N, PE: screw terminal for 0.5 ... 6 mm² single-core/finely stranded
● at output	+1, +2, -1, -2: screw terminal for 0.5 ... 6 mm²
mechanical data	
width × height × depth of the enclosure	30 × 124 × 117.2 mm
installation width × mounting height	40 mm × 184 mm
required spacing	
● top	40 mm
● bottom	20 mm
● left	5 mm
● right	5 mm
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
● DIN-rail mounting	Yes
● S7 rail mounting	No
● wall mounting	No
housing can be lined up	No
net weight	0.45 kg
additional information	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

Classifications

	Version	Classification
eClass	16	27-04-07-01
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	10	EC002540
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

Approvals Certificates

General Product Approval

Manufacturer Declaration

China RoHS

Subject to change without notice
© Copyright Siemens

last modified:	5/5/2026

Subject to change without notice
© Copyright Siemens