SIEMENS

Data sheet 6EP4347-7RC00-0AX0



SITOP RED1200/Red.M./24/48VDC/2X20A/EX

SITOP RED1200 redundancy module EX input/output: 24/48V DC/40 A Suitable for decoupling two SITOP power supplies with maximal per 20 A output current

General information	
Technical Product Detail Page	https://i.siemens.com/1P6EP4347-7RC00-0AX0
product brand name	SITOP
product type designation	RED1200
product designation	Redundancy module
input	
type of the power supply network	DC voltage
voltage curve at input	DC
supply voltage at DC	12 ... 48 V
input voltage at DC	10 ... 58 V
output	
voltage curve at output	Controlled DC voltage
number of outputs	1
output voltage at DC rated value	24 V
formula for output voltage	Vin - approx. 0.6 V
output voltage	
● at output 1 at DC rated value	24 V
output voltage	
● at output 1 at DC	12 ... 48 V
output voltage adjustable	No
output current	
● rated value	40 A
bridging of equipment	No
efficiency	
efficiency in percent	97.5 %
power loss [W]	
● at rated output voltage for rated value of the output current typical	25 W
● during no-load operation maximum	0.1 W
safety	
galvanic isolation between input and output	No
operating resource protection class	Class III
protection class IP	IP20
EMC	
standard	
● for emitted interference	EN 61000-6-3
● for interference immunity	EN 61000-6-2
standards, specifications, approvals	
certificate of suitability	

Subject to change without notice
© Copyright Siemens

● CE marking	Yes
● UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
● UKCA marking	Yes
● NEC Class 2	No
type of certification	
● CB-certificate	Yes
MTBF at 40 °C	6 100 000 h
standards, specifications, approvals hazardous environments	
certificate of suitability	
● IECEx	Yes; IECEx Ex ec IIC T4 Gc
● ATEX	Yes; ATEX (EX) II 3G Ex ec IIC T4 Gc
● ULhazloc approval	Yes
● UKEX	Yes
● CCC for hazardous zone according to GB standard	Yes
● FM registration	No
standards, specifications, approvals marine classification	
shipbuilding approval	No
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	No
● French marine classification society (BV)	No
● Det Norske Veritas (DNV)	No; in preparation
● Lloyds Register of Shipping (LRS)	No
standards, specifications, approvals Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	707.9 kg
● during manufacturing	22.3 kg
● during operation	685 kg
● after end of life	0.52 kg
ambient conditions	
ambient temperature	
● during operation	-40 ... +70 °C; with natural convection
● during transport	-40 ... +85 °C
● during storage	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
connection method	
type of electrical connection	push-in terminals
● at input	In1, In2: each for 0.75 ... 16 mm²
● at output	Out1: 0.75 ... 16 mm²
mechanical data	
width × height × depth of the enclosure	45 × 135 × 125 mm
installation width × mounting height	45 mm × 225 mm
required spacing	
● top	45 mm
● bottom	45 mm
● left	0 mm
● right	0 mm
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
● DIN-rail mounting	Yes
● S7 rail mounting	No
● wall mounting	No
housing can be lined up	Yes
net weight	0.51 kg
further information internet links	
internet link	
● to website: Industry Mall	https://mall.industry.siemens.com
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to web page: power supplies	https://siemens.com/sitop

Subject to change without notice
© Copyright Siemens

● to website: CAx-Download-Manager	https://siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

additional information

other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Classifications

	Version	Classification
eClass	16	27-04-07-01
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	10	EC002540
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

Approvals Certificates

Environmental Product Declaration

● global warming potential [CO2 eq] / during manufacturing	22.3 kg
● global warming potential [CO2 eq] / during operation	685 kg
● global warming potential [CO2 eq] / after end of life	0.52 kg
● global warming potential [CO2 eq] / total	707.9 kg

Environment | **General Product Approval**





Manufacturer Declaration





China RoHS

General Product Approval | **For use in hazardous locations**









Miscellaneous

CCC-Ex

Subject to change without notice
© Copyright Siemens

For use in hazard-ous locations	Maritime application
	 

last modified: 8/29/2026

© Copyright Siemens