SIEMENS

Data sheet 6ES7288-1ST32-0AA0



SIMATIC S7-200 SMART G2 CPU ST32, DC/DC/DC, slim design, onboard I/O: 16 DI 24 V DC; 16 DO 24 V DC; power supply: DC 20.4 - 28.8 V DC, program/data memory 100 KB motion enhanced with CAM, gear

General information	
Product type designation	CPU ST32 DC/DC/DC
Engineering with	
● Programming package	STEP 7 MICRO / WIN SMART V3.1
Installation type/mounting	
Rail mounting	Yes; Standard - DIN rail
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Rated value (AC)	
● 120 V AC	No
● 230 V AC	No
Input current	
Current consumption, max.	420 mA; 24 V DC
Inrush current, max.	15 A; at 28.8 V
Output current	
Current output, max.	300 mA; 24 V DC Sensor Power
for backplane bus (5 V DC), max.	1 680 mA; max. 5 V DC for EM bus
Storage	
Type of memory	DDR
Flash	Yes
RAM	No
Memory available for user data	100 kbyte
Memory size	100 kbyte
Micro Memory Card	Yes; microSDHC Card (optional)
Backup	
● present	Yes; Maintenance free, RTC requires 7 days.
CPU processing times	
for bit operations, typ.	90 ns; / instruction
for word operations, typ.	0.7 µs; / instruction
for floating point arithmetic, typ.	2.2 µs; / instruction
Address area	
I/O address area	
● Inputs	512 byte; 584 bit digital input 266 words analog input
● Outputs	512 byte; 584 bit digital output 266 words analog outputput
Time of day	
Clock	
● Type	Hardware clock, no battery backup

Subject to change without notice
© Copyright Siemens

● Hardware clock (real-time)	Yes
● Backup time	7 d
● Deviation per day, max.	120 s; within 120s/month at 25 °C
Digital inputs	
Number of digital inputs	16; Integrated
● of which inputs usable for technological functions	16; 8 single phase HSC 200 kHz; A/B phase HSC 200 kHz
Sourcing/sinking input	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	16
Input voltage	
● Type of input voltage	DC
● Rated value (DC)	24 V
● for signal "0"	I0.0 to I0.7 < 1 V DC; other channels < 5 V DC
● for signal "1"	I0.0 to I0.7 > 4 V DC; other channels > 15 V DC
Input current	
● for signal "0", max. (permissible quiescent current)	1 mA
● for signal "1", typ.	6 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.2 µs, 0.4 µs, 0.8 µs, 1.6 µs, 3.2 µs, 6.4 µs, 12.8 µs, 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms, 12.8 ms selectable
— at "0" to "1", min.	0.2 µs
— at "0" to "1", max.	12.8 ms
for interrupt inputs	
— Parameterizable	Yes
for technological functions	
— Parameterizable	Yes; 8 HSCs at 200 kHz for both signal phase and A/B phase
Cable length	
● shielded, max.	500 m; 50 m for technological functions
● unshielded, max.	300 m; for technological functions: No
Digital outputs	
Number of digital outputs	16; Transistor
● of which high-speed outputs	5; max. 200 kHz pulse train output
Switching capacity of the outputs	
● with resistive load, max.	0.5 A
● on lamp load, max.	5 W
Output voltage	
● for signal "0", max.	0.1 V
● for signal "1", min.	20 V DC
Output current	
● for signal "1" rated value	0.5 A
● for signal "0" residual current, max.	10 µA
Output delay with resistive load	
● "0" to "1", max.	0.5 µs
● "1" to "0", max.	2 µs
Cable length	
● shielded, max.	500 m
● unshielded, max.	150 m
Interfaces	
Number of industrial Ethernet interfaces	2
Number of RS 485 interfaces	1
1. Interface	
Interface type	PROFINET
Isolated	Yes; Transformer isolated, 1,500V AC
automatic detection of transmission rate	Yes; 100 Mbit/s
Autonegotiation	Yes
Autocrossing	Yes
Interface types	

Subject to change without notice
© Copyright Siemens

● RJ 45 (Ethernet)	Yes
● RS 485	Yes
Protocols	
● PROFINET IO Controller	Yes; Since V2.4
● PROFINET IO Device	Yes; I-Device since V2.5
PROFINET IO Controller	
● Transmission rate, max.	100 Mbit/s
Services	
— Number of connectable IO Devices, max.	8
— Updating time	4 ms; The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data.
Address area	
— Inputs, max.	128 byte; Per device
— Outputs, max.	128 byte; Per device
2. Interface	
Interface type	RS 485 (max. 187.5 kbps)
Interface types	
● RS 485	Yes
PROFIBUS DP master	
Services	
— S7 communication	Yes
Protocols	
PROFINET IO	Yes; RT Controller (since FW V2.4) & I-Device (since FW V2.5)
PROFIBUS	Yes; Via CM DP module
Protocols (Ethernet)	
● TCP/IP	Yes
Communication functions	
S7 communication	
● supported	Yes
● as server	Yes
● as client	Yes
Test commissioning functions	
Status/control	
● Status/control variable	Yes
Forcing	
● Forcing	Yes
Integrated Functions	
Counter	
● Number of counters	8
PID controller	Yes; PID closed-loop control function: continuous controller outputs, binary controller outputs, automatic/manual mode, max. 16 loops
Number of pulse outputs	5
Potential separation	
Potential separation digital inputs	
● between the channels, in groups of	2
Potential separation digital outputs	
● between the channels	No
● between the channels, in groups of	1
EMC	
Interference immunity against discharge of static electricity	
● Interference immunity against discharge of static electricity acc. to IEC 61000-4-2	Yes
— Test voltage at air discharge	8 kV
— Test voltage at contact discharge	4 kV
Interference immunity against high-frequency electromagnetic fields	
● Interference immunity against high-frequency radiation acc. to IEC 61000-4-3	Yes; 80 to 1 000 MHz, 10 V/m, 80 % AM at 1 kHz 1.4 to 6.0 GHz, 3 V/m, 80 % AM a 1 kHz
Interference immunity to cable-borne interference	
● Interference immunity on supply lines acc. to IEC 61000-	Yes; ±2 kV acc. to IEC 61000-4-4, Burst

© Copyright Siemens

4-4	
● Interference immunity on signal cables acc. to IEC 61000-4-4	Yes; ±2 kV acc. to IEC 61000-4-4, Burst
Interference immunity against voltage surge	
● Interference immunity on supply lines acc. to IEC 61000-4-5	Yes
● asymmetric interference	
— Test voltage on supply cables	500 V; line to line 500 V, line to earth 1 000 V
— Test voltage on signal cables >30m	1 000 V; for shielded cable
Interference immunity against conducted variable disturbance induced by high-frequency fields	
● Interference immunity against high frequency current feed acc. to IEC 61000-4-6	Yes; 10 V, 150 kHz to 80 MHz (to IEC 61000-4-6)
Emission of radio interference acc. to EN 55 011	
● Limit class A, for use in industrial areas	Yes; EN 61000-6-4, interference emission: Intended for use in industrial areas.
Emission of conducted and non-conducted interference	
● Interference emission via line/AC current cables	EN 61000-6-4, interference emission: Intended for use in industrial areas.
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Free fall	
● Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
● min.	-20 °C
● max.	60 °C
● horizontal installation, min.	-20 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-20 °C
● vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Air pressure acc. to IEC 60068-2-13	
● Storage/transport, min.	795 hPa
● Storage/transport, max.	1 139 hPa
Altitude during operation relating to sea level	
● Installation altitude, min.	-1 000 m
● Installation altitude, max.	2 000 m
Relative humidity	
● Operation at 25 °C without condensation, max.	95 %
Configuration	
Programming	
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
Dimensions	
Width	100 mm
Height	114 mm
Depth	75 mm
Weights	
Weight, approx.	305 g

Classifications

	Version	Classification
eClass	16	27-24-22-07
eClass	14	27-24-22-07
eClass	12	27-24-22-07

Subject to change without notice
© Copyright Siemens

eClass	9.1	27-24-22-07
eClass	9	27-24-22-07
eClass	8	27-24-22-07
eClass	7.1	27-24-22-07
eClass	6	27-24-22-07
ETIM	10	EC000236
ETIM	9	EC000236
ETIM	8	EC000236
ETIM	7	EC000236

Approvals / Certificates

General Product Approval








China RoHS

Manufacturer Declaration

General Product Approval	EMV	Environment
		

last modified: 6/22/2026

Subject to change without notice
© Copyright Siemens