SIEMENS

Data sheet 6DL1131-6BH00-0EH1

Siemens EcoTech

SIMATIC ET 200SP HA, digital input module, DI 16X24VDC HA, suitable for terminal block H1, M1, color code CC01, channel diagnostics



Figure similar

General information	
Product type designation	DI 16x24VDC HA
Firmware version	V1.0
● FW update possible	Yes
Usable terminal block	type H1, M1, N0, H0, M0 (for details see the system manual)
Color code for module-specific color-coded label	CC01
Product function	
● I&M data	Yes; I&M0 to I&M3
Engineering with	
● SPPA-T3000 can be configured/integrated from version	V8.0
Operating mode	
● DI	Yes
● Counter	No
● Oversampling	No
● MSI	No
Redundancy	
● Redundancy capability	Yes; With TB type M1
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	60 mA; without sensor supply
Current consumption, max.	120 mA; without sensor supply
Encoder supply	
Number of outputs	16
Output voltage, min.	18.2 V; L+ (-1 V)
Short-circuit protection	Yes; electronic (response threshold 0.7 A to 1.3 A; for IO redundancy up to 2.6 A) Ensure sufficient low-resistance cable routing to the sensor/actuator in order to attain the response threshold. Depending on the cable cross-section used, there may be constraints regarding the usable length of cable
Output current	
● up to 60 °C, max.	2 A; 1 A when mounted vertically; see derating information in Equipment Manual
● up to 70 °C, max.	1 A; See derating information in Equipment Manual

Subject to change without notice
© Copyright Siemens

24 V encoder supply	
● 24 V	Yes
● Short-circuit protection	Yes; electronic (response threshold 0.7 A to 1.3 A; for IO redundancy up to 2.6 A) Ensure sufficient low-resistance cable routing to the sensor/actuator in order to attain the response threshold. Depending on the cable cross-section used, there may be constraints regarding the usable length of cable
● Output current per channel, max.	0.5 A
● Output current per module, max.	2 A
Power	
Power consumption from the backplane bus	80 mW
Power loss	
Power loss, typ.	3.6 W; Maximum value (taking the max. encoder current and the max. operating voltage into account)
Address area	
Address space per module	
● Address space per module, max.	24 byte; Without SOE: PII: 2 bytes, +2 bytes for QI information, +1 byte of PROFINET status data; PIO: 1 byte of PROFINET status data; with SOE: PII: 2 bytes, +18 bytes for SOE (if 1 ms time stamp is used), +2 bytes for QI information, +1 byte of PROFINET status data; PIO: 1 byte PROFINET status data
Hardware configuration	
Automatic encoding	
● Mechanical coding element	Yes
Digital inputs	
Number of digital inputs	16
Digital inputs, parameterizable	Yes
Sourcing/sinking input	Yes; P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input characteristic curve in accordance with IEC 61131, type 2	No
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Pulse extension	Yes
● Length	off, 50 ms, 100 ms, 200 ms, 500 ms, 1 s, 2 s
Time stamp (with precision of 1 ms)	Yes; Resolution 1ms
Edge evaluation	Yes; rising edge, falling edge, edge change
Input voltage	
● Rated value (DC)	24 V
● for signal "0"	-30 to +5 V
● for signal "1"	+11 to +30V
Input current	
● for signal "1", typ.	2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; none / 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Encoder	
Connectable encoders	
● 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes; channel by channel
● Hardware interrupt	Yes; channel by channel
Diagnoses	
● Diagnostic information readable	Yes
● Monitoring the supply voltage	Yes; module-wise
— parameterizable	Yes
● Monitoring of encoder power supply	Yes
● Wire break	Yes; Channel-by-channel, optional protective circuit for preventing wire-break

© Copyright Siemens

	diagnostics in the case of simple encoder contacts: 15 kOhm to 18 kOhm
● Short-circuit to ground	Yes; Encoder supply to M, channel by channel
Diagnostics indication LED	
● MAINT LED	Yes; Yellow LED
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	Yes; red LED
● for module diagnostics	Yes; green/red LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	No
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C
● horizontal installation, max.	70 °C
● vertical installation, min.	-40 °C
● vertical installation, max.	60 °C
Dimensions	
Width	22.5 mm
Height	115 mm
Depth	138 mm
Weights	
Weight, approx.	135 g

Classifications

	Version	Classification
eClass	16	27-24-26-04
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599

Approvals / Certificates

General Product Approval

Miscellaneous | Declaration of Conformity

General Product Approval					For use in hazardous locations
China RoHS		Miscellaneous		Manufacturer Declaration	

Subject to change without notice
© Copyright Siemens

For use in hazardous locations

Declaration of Conformity

CCC

UL

IECEx

ATEX

Miscellaneous

Maritime application

ABS

BUREAU VERITAS

DNV

NK / Nippon Kaiji Kyokai

RINA

CCS (China Classification Society)

Environment

EPD

Siemens EcoTech

last modified: 3/10/2026

Subject to change without notice
© Copyright Siemens