Data Sheet | Item Number: 258-5107

Thermal transfer printer; Smart Printer; for complete control cabinet marking; Starterkit; With marking material

https://www.wago.com/258-5107

This item includes:



Item No.: 258-5005 — 1

Thermal transfer ink ribbon; for Smart Printer; black



Item No.: 258-5006 — 1

Roller; for Smart Printer; for marking strips, device and equipment markers, conductor and cable markers



Item No.: 258-5007 — 1

Roller; for Smart Printer; for WMB-Inline WAGO (2009-115, -114, -113); 1 grinding device

Item No.: 2009-110 — 1

Marking strips; for Smart Printer; 50 m on roll; not stretchable; plain; snap-on type; white



Item No.: 2009-115 — 1

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

System requirements

Memory	4 GB
Supported operating systems	Windows 7 Windows 8 Windows 10 Windows 11 Linux®

Technical data

Print head	Glass layer, spring-mounted
Print resolution	300 dpi
Print resolution	300 dpi (12 pixels/mm)
Print speed	Max. 127 mm/s (WAGO recommends 50.8 mm/s)
Print width	47 mm
Print length (max.)	762 mm
See-through/reflective sensor	Yes, centrally mounted
Memory	8192 MB
Interfaces	USB type A, (for BT and Wi-Fi connection), USB type B (for PC connection), RS-232, ETHERNET 10/100 Mbps
Operating voltage	100 … 240 VAC, 50 … 60 Hz (automatic adjustment)
Safety approvals	CE (EMC)
Operating display	Color TFT LCD with navigation button
Ink ribbon	Roll outer diameter: 40 mm; Core inner diameter: 12.7 mm (0.5 inch); Max. length: 110 m; Max. width: 58 mm
Ink ribbon length	360.9
Scope of delivery	Power supply + cable, 2 rollers (258-5006 + 258-5007), 1 reel holder, 1 ink ribbon (258-5005), Smart Script marking software and driver, USB cable, external unwinder, 1 empty cardboard core, 1 reel each of marking strips (2009-110) and WMB Inline markers (2009-115)

Continued on next page

Physical data

Height	175 mm / 6.89 inches
Width	135 mm / 5.315 inches
Depth	245 mm / 9.646 inches

Material data

Weight	3840 g
Fire load	10.153 MJ

Environmental requirements

Ambient temperature (storage)	-20 … +50 °C
Ambient temperature (operation)	+5 … +40 °C

Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	TW
GTIN	4066966520644
Customs tariff number	84433210000

Product Classification

UNSPSC	43212108
ETIM 9.0	EC000610
ETIM 10.0	EC000610
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption