Product data sheet
Characteristics

RXZE2M114M
socket, Harmony Electromechanical Relays, for RXM2 RXM4 relays, screw connec to rs, mixed contact



Main

Range of product	Harmony Electromechanical Relays Harmony Timer Relays
Product compatibility	Plug-in relay RXM with 2 C/O contact[RETURN]Plug-in relay RXM with 4 C/O contact[RETURN
Device short name	RXZ
[Ith] conventional free air thermal current	10 A
Product or component type	Socket
Contacts type and composition	4 C/O

Complementary

[Ue] rated operational voltage	< 250 V conforming to IEC < 300 V conforming to UL
Connections - terminals	Screw connectors, 1 x 0.34...1 x 2.5 mm² (22 AWG...14 AWG) flexible with cable end Screw connectors, 2 x 0.34...2 x 1 mm² (22 AWG...17 AWG) flexible with cable end Screw connectors, 1 x 0.5...1 x 2.5 mm² (20 AWG...14 AWG) solid without cable end Screw connectors, 2 x 0.5...2 x 1.5 mm² (20 AWG...16 AWG) solid without cable end
Shape of pin	Flat
Tightening torque	< 1 N.m for M3 screw(s)
Fixing mode	By screw (panel) Clip-on (35 mm symmetrical DIN rail)
Wire stripping length	8 Mm
Contact terminal arrangement	Mixed
[Uimp] rated impulse withstand voltage	4 KV
Overvoltage category	III
Pollution degree	3
Sale per indivisible quantity	10
Width	27 Mm
Net weight	0.055 Kg

Environment

IP degree of protection	IP20 conforming to IEC 60529
Dielectric strength	2500 V
Standards	IEC 61984
Product certifications	UL[RETURN]CSA[RETURN]Lloyd's
Marking	CE
Ambient air temperature for storage	-40…85 °C
Ambient air temperature for operation	-40…55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.300 Cm
Package 1 Width	2.700 Cm
Package 1 Length	7.500 Cm
Package 1 Weight	55.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	7.800 Cm
Package 2 Width	9.000 Cm
Package 2 Length	14.400 Cm
Package 2 Weight	584.000 G
Unit Type of Package 3	S03
Number of Units in Package 3	230
Package 3 Height	30 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm
Package 3 Weight	13.694 Kg

Offer Sustainability

Recyclability potential, in %	46
Total lifecycle Carbon footprint	0.6 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.42739931436854195
Carbon footprint of the manufacturing phase [A1 to A3]	0.4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.04471793861273453
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.00032309219340593355
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.1492624380704362
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is know
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised