Product data sheet
Characteristics

TM3AQ4G
analog output module, Modicon TM3, 4 outputs, spring, 24V DC



Main

Range of product	Modicon TM3
Product or component type	Analog output module
Range compatibility	Modicon M221 Modicon M241 Modicon M251 Modicon M262
Analogue output number	4

Complementary

Analogue input resolution	12 bits 11 bits + sign
Stabilisation time	1 Ms
Analogue output type	Current: 4...20 mA Current: 0...20 mA Voltage: 0...10 V Voltage: - 10...10 V
Conversion time	1 ms + 1 ms per channel + 1 controller cycle time
Absolute accuracy error	+/- 1 % of full scale +/- 0.2 % of full scale at 25 °C
Repeat accuracy	+/- 0.4 %FS
Output ripple	20 mV
Cross talk	<= 1 LSB
Type of cable	Twisted shielded pairs cable <30 m for output circuit
Electrical connection	11 x 2.5 mm² removable spring terminal block with pitch 5.08 mm adjustment for outputs and su
LSB value	2.44 mV, 0...10 V 4.88 mV, - 10...10 V 4.88 µA, 0...20 mA 3.91 µA, 4...20 mA
Insulation	Between output and supply at 1500 V AC Between output and internal logic at 500 V AC
Immunity to microbreaks	10 Ms
Load impedance ohmic	1 kOhm voltage 300 Ohm current
Load type	Resistive
Temperature drift	+/- 0.01 %FS/°C
Non-linearity	+/- 0.2 %FS
Typical current consumption	40 MA at 5 V DC no load 50 MA at 5 V DC full load 50 MA at 24 V DC no load 125 MA at 24 V DC full load
Local signalling	1 LED green for PWR

Mounting support	Top hat type TH35-15 rail conforming to IEC 60715 Top hat type TH35-7.5 rail conforming to IEC 60715 plate or panel with fixing kit
Height	90 Mm
Width	23.6 Mm
Depth	70 Mm
Net weight	0.1 Kg

Environment

IP degree of protection	IP20
Marking	CE
Product certifications	CE[RETURN]UKCA[RETURN]RCM[RETURN]EAC[RETURN]CULus[RETURN]CULus HazLoc
Standards	IEC 61131-2
Electromagnetic emission	Radiated emissions - test level: 40 dBµV/m QP class A (10 m) at 30…230 MHz conforming to IEC Radiated emissions - test level: 47 dBµV/m QP class A (10 m) at 230…1000 MHz conforming to
Ambient air temperature for operation	-10…55 °C (horizontal installation) -10…35 °C (vertical installation)
Ambient air temperature for storage	-25…70 °C
Relative humidity	10…95 % without condensation
Operating altitude	0...2000 m
Pollution degree	2
Vibration resistance	3.5 mm (f = 5…8.4 Hz) on DIN rail 3 gn (f = 8.4…150 Hz) on DIN rail
Shock resistance	15 gn for 11 ms

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 Cm
Package 1 Width	12.5 Cm
Package 1 Length	10.5 Cm
Package 1 Weight	200.0 G
Unit Type of Package 2	S02
Number of Units in Package 2	9
Package 2 Height	15 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	2.316 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	288
Package 3 Height	75 Cm
Package 3 Width	120 Cm
Package 3 Length	80 Cm
Package 3 Weight	83 Kg

Offer Sustainability

Recyclability potential, in %	3
Total lifecycle Carbon footprint	60 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	13.788566778647954
Carbon footprint of the manufacturing phase [A1 to A3]	14 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.04765490592624833
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.00561993731636851
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	45.53523314102323
Carbon footprint of the use phase [B2, B3, B4, B6]	46 kg CO2 eq.
Toxic heavy metal free	Yes

Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.5102658984244621
Carbon footprint of the end-of-life phase [C1 to C4]	0.5 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	60
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	7cc01735-94b8-432b-9a81-f9da4dd7709d
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, wh
PVC free	Yes
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised